


Unit : mm

Marking (EX)



SIZE B (A)	d	L	ASME B16.5 Class 300 FLANGE						H	W	重量 (kg)	備考
			D	C	g	t	f	n-φh				
2" (50)	51	267	165	127	92	23	1.6	8-19	385	200	30	
2½" (65)	64	292	190	149	105	26	1.6	8-22	420	280	42	
3" (80)	76	318	210	168	127	29	1.6	8-22	440	280	55	
4" (100)	102	356	254	200	157	32	1.6	8-22	515	350	90	

				Nominal Pressure	Class 300
				Test Press. of Shell	7.8 MPa
				Test Press. of Seat	5.7 MPa
				Max. Working Temp.	425 °C
				Apply Medium	Water Steam Oil
Design and Manufacture Standard					
				Design and Manufacture Standard	BS 1873
				Test & Inspection	API 598
				Face to Face Dimension	ASME B16.10
				Flange Dimension	ASME B16.5

PART NO.	PART NAME	MATERIAL	Q'TY	REMARK
24	LANTERN RING	A182-F6a	1	
18	HANDLE NUT	S35C	1	
17	HANDWHEEL	Ductile Iron	1	
16	SLEEVE	A439-D2	1	
15	NUT	A194 2H	2	
14	EYE BOLT	A193 B7	2	
13	GLAND FLANGE	A216-WCB	1	
12	GLAND	A182-F6a	1	
11	PACKING	GRAPHITE	1s	T#2205+2250 Eq.
10	BACK SEAT	A182-F6a	1	
9	BONNET	A216-WCB	1	
8	GASKET	Graphite	1	Spiral Wound
7	BONNET BOLT	A193 B7		
6	BONNET NUT	A194 2H		
5	DISC NUT	A182-F6a	1	
4	STEM	A182-F6a	1	
3	DISC	A105	1	Stellite Faced
2	SEAT RING	A105	1	Stellite Faced
1	BODY	A216-WCB	1	

PART NO. PART NAME MATERIAL Q'TY REMARK			
CAST STEEL ASME B16.5 CLASS 300			
MANUAL OPERATED GLOBE VALVE			
OUTSIDE SCREW STEM			
SIZE 2B-4B			
APPROVED BY	CHECKED BY	DRAWN BY	DRAWING No.
F.Makimura	M.Toyama	H.Hosoi	HCH010423
MAY.16.2009	MAY.16.2009	MAY.16.2009	
MAKIMURA MFG CO LTD			
HIKONE SHIGA JAPAN			